

Penguin Wee

Compatible operating systems	Ubuntu & Other GNU/Linux distributions
Processor	Intel Atom 1.6Ghz
Chipset	Intel 945GC Express / Intel ICH7
Graphics & Video Module	Intel GMA 950
Main Memory	DDR2 SDRAM (2GB Max) PC2-3200, PC2-4300, PC2-6400, PC2-5300
Expansion Slots	1 PCI
Storage Interfaces	Serial ATA-300 - connector(s): 2 x 7pin Serial ATA - 2 device(s) ATA-100 - connector(s): 1 x 40pin IDC - 2 device(s)
Other Interfaces	4 x Hi-Speed USB - 4 pin USB Type A 1 x serial - RS-232 - 9 pin D-Sub (DB-9) 1 x parallel - IEEE 1284 (EPP/ECP) - 25 pin D-Sub (DB-25) 1 x display / video - VGA - 15 pin HD D-Sub (HD-15) 1 x mouse - generic - 6 pin mini-DIN (PS/2 style) 1 x keyboard - generic - 6 pin mini-DIN (PS/2 style) 1 x network - Ethernet 10Base-T/100Base-TX - RJ-45 1 x audio - line-in - mini-phone 3.5 mm 1 x microphone - input - mini-phone 3.5 mm 1 x audio - line-out - mini-phone stereo 3.5 mm
Form Factor	Mini ITX / micro ATX
Audio	Realtek ALC662 Stero Output
Max Bus Speed	533 MHz
Networking	Fast Ethernet
BIOS Features	ACPI support, rapid BIOS boot, SMBIOS support
Hardware Monitoring	CPU core temperature, chassis temperature, CPU fan tachometer, chassis fan tachometer, system voltage
Sleep	Keyboard wake up, mouse wake up, wake on PCI device, wake on USB port